



MIG WELDING GUIDE



Series	Page	Model	Double Pulse	Synergic	MIG/MAG	Flux-cord	STICK	HF TIG	AC TIG	DC TIG	Lift TIG	Spool gun	Push pull gun	Wire feeder type	Wire size (mm)	Input voltage (V)	Welding output range(A)
I Welding	P30	POWERMIG 200 LCD		■	■	■	■				■	■		Built-in	0.6-1.2	90-275	10-200
	P22	4 IN 1		■	■	■	■	■	■	■	■	■		Built-in	0.6-1.2	90-275	10-200
	P23	TrollyMIG 315		■	■	■	■				■	■		Built-in	0.8-1.2	380/400/415±15%	10-300
	P24	MULTIMIG 350		■	■	■	■				■	■		Separate	1.0-1.6	380/400/415±15%	10-350
	P24	MULTIMIG 500		■	■	■	■				■	■		Separate	1.0-1.6	380/400/415±15%	10-500
	P25	MULTIMIG 250 DP	■	■	■	■	■				■	■	■	Built-in	0.8-1.2	90-275	30-250
	P26	TROLLYMIG 3006 DP	■	■	■	■	■				■	■	■	Built-in	0.8-1.2	380/400/415±15%	30-300
	P27	MULTIMIG 350 DP	■	■	■	■	■				■	■	■	Separate	1.0-1.6	380/400/415±15%	30-350
	P27	MULTIMIG 500 DP	■	■	■	■	■				■	■	■	Separate	1.0-1.6	380/400/415±15%	40-500
	P28	MULTIMIG 400 MV		■	■	■	■				■	■		Separate	1.0-1.6	200-660	30-400
	P29	MULTIMIG 500 MV		■	■	■	■				■	■		Separate	1.0-1.6	200-600	40-500
P Welding	P64	DELTA MIG 350			■		■							■	0.8-1.2	380/400/415±15%	60-350
	P64	DELTA MIG 500			■		■							■	1.0-1.6	380/400/415±15%	60-500
	P64	DELTA MIG 630			■		■							■	1.0-1.6	380/400/415±15%	60-630
	P65	DELTA MIG 350S		■	■		■							■	0.8-1.2	380/400/415±15%	60-350
	P65	DELTA MIG 500S		■	■		■							■	1.0-1.6	380/400/415±15%	60-500
	P65	DELTA MIG 630S		■	■		■							■	1.0-1.6	380/400/415±15%	60-630
	P66	DELTA MIG 350CL		■	■									■	0.8-1.2	380/400/415±15%	60-350
	P66	DELTA MIG 500CL		■	■									■	1.0-1.6	380/400/415±15%	60-500
	P66	DELTA MIG 630CL		■	■									■	1.0-1.6	380/400/415±15%	60-630
	P67	DELTA MIG 280DP	■	■	■		■							■	0.6-1.0	380/400/415±15%	20-280
	P67	DELTA MIG 350DP	■	■	■		■							■	0.6-1.2	380/400/415±15%	20-350
	P67	DELTA MIG 500DP	■	■	■		■							■	0.6-1.6	380/400/415±15%	20-500
S Welding	P78	AUTOPOWER 120			■	■	■				■			Built-in	0.6-1.0	220/230/240±15%	20-120
	P78	AUTOPOWER 140			■	■	■				■			Built-in	0.6-1.0	220/230/240±15%	20-140
	P79	AUTOPOWER 160			■	■	■				■			Built-in	0.6-1.0	220/230/240±15%	20-160
	P79	AUTOPOWER 182			■	■	■							Built-in	0.6-1.2	220/230/240±15%	20-180
	P79	AUTOPOWER 200			■	■	■							Built-in	0.6-1.2	220/230/240±15%	20-200
	P79	AUTOPOWER 202			■	■	■							Built-in	0.6-1.2	220/230/240±15%	20-300