

150A



Brass-2264

SPECIFICATIONS

Model	ERP	cable section (mm ²)	Max. Current (A)	Weight (g)
Brass-2264	00.2264	6-25	150	150

300A



Brass-0161



Brass-0162



Brass-0104



Brass-0146



Brass-0207



Brass-0208



Brass-0164



Brass-0165



Brass-0166

SPECIFICATIONS

Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Brass-0161	300	45	275
Brass-0162	300	45	267
Brass-0104	300	59	693
Brass-0146	300	40	371
Brass-0207	300	41.53	460
Brass-0208	300	41.53	460
Brass-0164	300	28	376
Brass-0165	300	28	369
Brass-0166	300	35	380

500A



Brass-0117



Brass-0167



Brass-0168




Brass-0114



Brass-1010



Brass-1011



Brass-0170



Brass-0171



Brass-0105



Brass-0113




Brass-0172



Brass-0173



Brass-0101



Brass-0175



Brass-0176



Brass-0107



Brass-0177



Brass-0103



Brass-0178




Brass-0197

SPECIFICATIONS

Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Brass-0117	500	59	600
Brass-0167	500	59	615
Brass-0168	500	40	644
Brass-0114	500	66	1060
Brass-1010	500	/	1042
Brass-1011	500	45	424
Brass-0170	500	45.25	417
Brass-0171	500	58	650
Brass-0105	500	58	706
Brass-0113	500	58	715
Brass-0172	500	35	750
Brass-0173	500	40	552
Brass-0101	500	66	2015
Brass-0175	500	/	1103
Brass-0176	500	/	889
Brass-0107	500	37	664
Brass-0177	500	37	661
Brass-0103	500	37	619
Brass-0178	500	37	629
Brass-0197	500	37	640

600A



Brass-0109



Brass-0102

SPECIFICATIONS

Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Brass-0109	600	40	837
Brass-0102	600	36	780

800A



Brass-0179



Brass-0174



Brass-0209


SPECIFICATIONS

Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Brass-0179	800	37.5	1055
Brass-0174	800	37.99	2000
Brass-0209	800	37	1054

1000A



Brass-0180




Brass-0181




Brass-0182



Brass-0183



Brass-0200



Brass-0210

SPECIFICATIONS

Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Brass-0180	1000	70	657
Brass-0181	1000	65	1247
Brass-0182	1000	66	3000
Brass-0183	1000	56	2250
Brass-0200	1000	115	4105
Brass-0210	1000	140	6317

1200A




Brass-0184


SPECIFICATIONS

Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Brass-0184	1200	56	1428

1500A



Brass-0185



Brass-0186



Brass-0187



Brass-0188



Brass-0212




Brass-0213

SPECIFICATIONS

Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Brass-0185	1500	140	4500
Brass-0186	1500	115	2275
Brass-0187	1500	140	8500
Brass-0188	1500	115	6230
Brass-0212	1500	135	5000
Brass-0213	1500	140	8000

2000A



Brass-0199




Brass-0211


SPECIFICATIONS

Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Brass-0199	2000	140	11000
Brass-0211	2000	110	8622

2500A



Brass-0189



Brass-0190



Brass-0202

SPECIFICATIONS

Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Brass-0189	2500	77	7300
Brass-0190	2500	110	10300
Brass-0202	2500	/	10600

Brass Rotary Device for Earth Clamp



Brass Connector-0201



Brass Connector-0191



Brass Connector-0192



Brass Connector-0193



Brass Connector-0194



Brass Connector-0195



Brass Connector-0153



Brass Connector-0196

SPECIFICATIONS

Model	Max. Current (A)	Size (mm)	Weight (g)
Brass Connector-0201	500	97	443
Brass Connector-0191	500	140	923
Brass Connector-0192	1000	110	950
Brass Connector-0193	1000	110*120	1830
Brass Connector-0194	1000	103*120	1829
Brass Connector-0195	1000	115*120	1889
Brass Connector-0153	1500	140*170	4000
Brass Connector-0196	2000	165	6500